



# SkyConnector Mini

## Economical Broadband Wireless CPE

If you are looking to provide economical broadband wireless, you'll find it with the SkyConnector™ Mini. Like DSL and cable modems, the SkyConnector Mini is customer premise equipment (CPE) designed for business or residential subscribers; however, instead of requiring copper or coaxial wires, the SkyConnector Mini uses the unlicensed 5 GHz spectrum to provide DSL- and cable-like broadband connectivity. When combined with SkyPilot's broadband wireless base stations, the SkyConnector Mini provides high-speed services over large coverage areas at a surprisingly low cost.


Since per-subscriber expenses are so critical to a service provider's business model, the SkyConnector Mini is designed to minimize costs while simultaneously providing industry-leading capabilities. The SkyConnector Mini's low per-unit price also comes with expense-reducing features such as "zero-touch" configuration, which combines visual feedback of signal strength with auto-discovery and auto-provisioning features to ensure proper installation and minimize deployment and ongoing operational costs.

But don't let the SkyConnector Mini's low total cost-of-ownership fool you – it also includes the features of competitive broadband wireless CPEs that cost 5 times as much. The SkyConnector Mini comes standard with OFDM modulation and hardware-based AES encryption on all wireless links, ensuring both non-line-of-sight (NLOS) and hack-proof security. It also features SkyPilot's unique SyncMesh™ protocol, which synchronizes all wireless communications to minimize interference, maximize spectral capacity, and ensure deterministic traffic flows to guarantee latency-sensitive applications like Voice-over-IP (VoIP). And since the SkyConnector Mini is part of SkyPilot's Layer 2 broadband wireless backhaul network, it even has advanced traffic management capabilities such as per-subscriber rate limiting and virtual LAN (VLAN) segmentation. All of this in a compact package that can operate anywhere over the entire 5.250-6.075 GHz frequency range and has a variety of mounting options for flexible installation.

So, if you are seeking the most cost-effective and feature-rich broadband wireless CPE available, look no further than the SkyConnector Mini.

## Benefits

- **Low Cost – economical** broadband wireless CPE
- **Long Range** – high-power (38 dBm EIRP) enables links at distances up to **7.5 miles/12 km**
- **High Capacity** – up to **13 Mbps** of throughput
- **Non-Line of Sight (NLOS)** – standard **OFDM** leverages multipath for NLOS connectivity
- **Synchronous QoS** – deterministic traffic flows guarantees applications like **VoIP**
- **Secure Connectivity** – all wireless links hardware encrypted with **AES**
- **Frequency Flexibility** – each unit can operate anywhere from **5.250 to 6.075 GHz**
- **"Zero-Touch" Configuration** – auto-discovery and auto-provisioning minimizes operational expenses
- **Traffic Management** – Layer 2 networking with per-subscriber rate limiting and virtual LANs



*SkyConnectors provide broadband wireless services to fixed locations like office buildings and houses.*

## SkyConnector Mini Specifications

### Traffic Management

- VLAN support: IEEE 802.1q
- Traffic Prioritization: IEEE 802.1p, protocol type, IP port, IP ToS field, and IP address list
- Traffic Filtering: protocol type, IP port, and IP address list
- Traffic Shaping: upstream and downstream per-user rate control

### Configuration, Management, & Monitoring

- NMS integration: SNMPv2c
- EMS: SkyControl™
- IP address: DHCP or static
- Firmware: Multiple versions stored in nonvolatile memory; updated over the air via FTP
- Provisioning: Manual or automated
- Configuration file: XML over HTTP
- MIB support: MIB-II (RFC 1213); EtherLike (RFC 2665); Bridge (RFC 1493); SkyPilot private MIB
- Remote management: CLI via Telnet, SNMPv2c

### Wireless

<b>Frequency band</b>	5.250-6.075 GHz
<b>Transmit power</b>	30 dBm/1W (peak)/24 dBm/250mW (average)
<b>Antenna</b>	14 dBi (55° azimuth x 18° elevation)/vertical polarity
<b>EIRP</b>	44 dBm/25 W (peak)/38 dBm/6 W (average)
<b>Receive sensitivity</b>	-94 dBm at 6 Mbps modulation
<b>Range</b>	Up to 7.5 miles (12 km)
<b>Media access</b>	Time Division Duplex (TDD)
<b>Modulation technique</b>	OFDM with adaptive modulation
<b>Modulation rates</b>	54, 48, 36, 24, 18, 12, 9, and 6 Mbps
<b>Throughput</b>	Up to 13 Mbps TCP/20 Mbps UDP (at 36 Mbps modulation rate)
<b>Latency</b>	8-10 ms roundtrip per hop
<b>Channel width</b>	20 MHz
<b>Channel resolution</b>	5 MHz frequency control
<b>Authentication</b>	RSA-based certificates
<b>Encryption</b>	128-bit AES

### Product Specifications

<b>Enclosure</b>	Outdoor UV stabilized plastic
<b>Connectors</b> (under waterproof sliding door)	RJ-45 to 12V/1A Power over Ethernet (PoE) injector (Optional) reverse-polarity SMA to external antenna
<b>Power</b>	100-240 VAC, 50-60 Hz input; 5 Watts
<b>Mounting</b>	Pole mount (standard), wall mount (optional), or window suction mount (optional)
<b>LEDs</b>	Power, Ethernet, and wireless signal strength
<b>Dimensions</b>	10.4" (26 cm) H x 3.2" (8 cm) W x 1.2" (3 cm) D
<b>Weight</b>	0.9 pounds (0.4 kg)
<b>Operating temperature</b>	-4° to 158° F (-20° to 70° C)
<b>Operating humidity</b>	5 to 95% condensing
<b>Certifications</b>	FCC Part 15.247, IC RS210, CE, ETSI 300-019-1.4 shock and vibration, RoHS
<b>Warranty</b>	One-year limited warranty on hardware; 90-day limited warranty on software



Copyright © 2010 Trilliant Incorporated. ALL RIGHTS RESERVED. SkyConnector™, SkyControl™, SkyExtender®, SkyGateway™, SkyPilot®, SyncMesh™, the SkyPilot logo, and the Trilliant logo are trademarks of Trilliant Incorporated and/or its subsidiaries. All other trademarks are the property of their respective owners. This material is provided for informational purposes only; Trilliant assumes no liability related to its use and expressly disclaims any implied warranties of merchantability or fitness for any particular purpose. All specifications, descriptions, and information contained herein are subject to change without prior notice.  
100304

Trilliant Incorporated  
1100 Island Drive  
Redwood City, CA 94065 USA  
+1.650.204.5050  
SkyPilotSales@TrilliantInc.com  
www.trilliantinc.com